



VINTAGE WOODS  
AUTHENTIC • ORGANIC

## VINTAGE WOODS MAINTENANCE COATING

### HOW MUCH DO I NEED?

A gallon of this house stain will cover 100-200 sq. ft. of rough/porous surface or 350 sq. ft. of smooth surface. Measure the width of each side and multiply by the height of the side. Divide the total area of the sides by either 200 or 350 according to the surface texture, to get the number of gallons needed. Be sure to subtract out the area covered by windows, doors and other trim.

### HOW DO I USE THIS?

- Protect surrounding structures and paints with drop cloths.
- Stain on a shaded side of the building. Do not apply if the temperature is below 35°F, or above 90°F, or if rain is expected within 3 hours.
- Stir thoroughly.
- Apply without reducing, using a sprayer, roller, pad or brush.
- Stain the wall area first, then the trim/windows, starting at the top and working down.
- Stain from a dry area into the adjoining wet stain area.
- Clean wet stain from hands and tools and any spills and splatters immediately with soap and water.

### IMPORTANT TIPS:

All stains tend to lap (dark lines where two freshly coated areas over-lap).

### TO MINIMIZE LAPPING:

- Do not stain in direct sun or on a hot surface.
- Stain from a dry area into the adjoining wet stain area.
- Stain up and down vertical wall siding and across horizontal wall siding.
- Do not use on horizontal surfaces such as roofs, floors and decks.

Vintage Woods, Inc.  
210 Airpark Drive • Gypsum, CO 81637  
970.524.4041  
[www.vintagewoodsus.com](http://www.vintagewoodsus.com)



= 100-200  
sq. ft.  
rough/  
porous

or 350 sq. ft.  
smooth  
surfaces

### CAUTIONS

Use only with adequate ventilation. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

**FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

**WARNING:** This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm.

**DO NOT TAKE INTERNALLY.  
KEEP OUT OF REACH OF CHILDREN.**

**FOR EXTERNAL USE ONLY.  
KEEP FROM FREEZING.**

**NON-PHOTOCHEMICALLY REACTIVE**

CAS NO.	INGREDIENT
7732-18-5	Water
Proprietary	Acrylic Polymer
12736-96-8	Nepheline Syenite
29911-28-2	1-(2-Butoxymethylethoxy)-propanol
107-21-1	Ethylene Glycol
14464-46-1	Cristobalite

VOC: 193 g/L - 1.61 lb/gal as per 40 CFR 59.406

*\*When it comes time to maintain or if wear and tear is starting to show. Materials can be ordered through Vintage Woods for specific color formulas. A video conference call is recommended with your painting contractor to review application advice. All custom formulas are saved to your project file. Apply per specifications on product label.*